

ceado.

Rev Zero




Designing **Flavor.**


The ideal grinder
to enhance **flavor
clarity**, making it
perfect for specialty
coffee enthusiasts.

RSZ83

83 mm Red Speed
coated burrs with
lifespan of 4 tons.



Particle Size Distribution of Rev Zero



Sweep Out Dual Spin



The Sweep-Out technology **eliminates coffee retention**, keeping every dose fresh and full of flavor.

- Preserves **volatile** compounds, enhancing aroma and complexity in the cup.
- Delivers **99% of ground coffee** into the portafilter, maximizing flavor clarity and consistency.
- **Prevents variability** caused by retained grounds affecting temperature, gas content, and taste.
- **Minimizes retention to just ~2g** between the burrs (vs. 9–13g in other grinders), saving 3–5 doses per day.
- Works in **synergy with GTM, WAM,** and **Steady Lock** technologies to maintain consistent dosing and grind size in all conditions.



Weight Adjustment Module

WAM

Consistent weight aids in building and monitoring flavour recipes. The Rev Series feature an **interchangeable weight module**, that can be mounted in under two minutes, even post grinder installation.



WAM Module




PFA Module

Grounds Temperature Management




Stable and **low coffee grounds temperature** is key for consistent flavor extraction.

- ❶ **2.5 kg heat sink** around the burrs to constantly remove large amounts of heat.
- ❷ **Shaft** separates burrs from motor to prevent heat transmission.
- ❸ **Insulation** to prevent heat transmission through the shaft.
- ❹ **Active internal airflow management** to support temperature stability at any pace.




Peak Hour

800 g - 40 Doses Per Hour



Stress Test


2,4 kg - 120 Doses Per Hour




Steady Lock



The grinder features a counteracting system that **expands in the opposite direction** of the burrs, neutralizing the effect of heat expansion. This ensures a consistent particle size at any pace, preserving the same flavor profile.



Peak Hour
Granulometry Consistency



Noise Reduction



Grinder built to **prevent vibration transmission** and **noise emissions**.

- ❶ **2.5 kg grind chamber** for higher noise insulation.
- ❷ **Rubber rings** to reduce noise propagation.
- ❸ **Motor separated from burrs** to prevent vibration transmission.
- ❹ Motor mounted on **suspension system** reduces vibration emission.



Advanced Leveling Intelligent Grinding Nexus

Align

High-precision **stepless adjustment with display** for a digital, intuitive, and quick reading of the grind setting.



Cleaning has never been easier.

Burrs are easy to clean and inspect as it takes only **3 screws** to remove the top of the grind chamber. No grind re-adjustment is needed after cleaning.



Removable Chute

It only takes **few seconds and a screwdriver** to loosen the safety screw and extract the chute along with the metal flap for cleaning. Putting it back is as easy: **four guides** quickly bring it back to the correct position with no chance of error.


Removable Air Filter

To prevent dust and dirt entering the inner parts of the grinder, an air filter is installed behind the air suction grid. A **cleaning reminder** periodically appears on display.



The user interface is designed to be state-of-the-art, ensuring **intuitive use** for all.


**Scroll
Down Menu**




Customizable Dose Layout




User Interface




Programmable Air Flow



Maintenance Alerts



**Five Grinding Activation
Modes**



General Settings

- Ground temperature stability
- Weight precision
- Granulometry consistency
- Zero Retention

The grinder that designs flavor.



© Ceado srl - All Rights Reserved - 02/2025

**Ceado original burrs
RSZ83**

Rev Zero

ø 83 Red Speed flat burrs



Align



Steady Lock



Gtm



WAM



Sweep Out
Dual Spin

Technical data

Voltage - Power	220-240 V • 50-60 Hz / 900 W 110-120 V • 60 Hz / 7 A
Rpm 50 Hz / 60 Hz	1480 / 1700 rpm
Average Output (g/s)	5,2 (50 Hz) / 6 (60 Hz)
Net weight	17 kg
Gross weight	18,8 kg
Dimensions	200 x 270 x 630h mm
Burrs	RSZ83 ø 83 Red Speed flat burrs*
Hopper	Approximately 1600 g
Dose setting	Digital with grind reference on display
Display	Multifunction Touch
Noise	62 dB
Colors	● ●



*NSF version uses Steel burrs.

Rev Zero Webpage